

SEETEC EVA VA600

Ethylene Vinyl Acetate Copolymer

Lotte Chemical Corporation

PROSPECTOR®

www.ulprospector.com

Technical Data

Product Description

SEETEC VA600 resin is produced by ExxonMobil Chemical's autoclave process technology. SEETEC VA600 resin, with 28% VA content, is an excellent raw material in the application of hot melt adhesives.

General

Material Status	• Commercial: Active
Literature ¹	• Technical Datasheet (English)
Search for UL Yellow Card	• Lotte Chemical Corporation • SEETEC EVA
Availability	• Asia Pacific • Europe • North America
Additive	• Antioxidant
Features	• Antioxidant
Uses	• Adhesives
RoHS Compliance	• RoHS Compliant

Physical	Nominal Value Unit	Test Method
Density	0.950 g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	6.0 g/10 min	ASTM D1238
Vinyl Acetate Content	28.0 wt%	Internal Method
Hardness	Nominal Value Unit	Test Method
Durometer Hardness (Shore D)	26	ASTM D2240
Thermal	Nominal Value Unit	Test Method
Vicat Softening Temperature	42.0 °C	ASTM D1525
Melting Temperature	71.0 °C	Internal Method

Notes

¹ These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

² Typical properties: these are not to be construed as specifications.



SEETEC EVA VA600

Ethylene Vinyl Acetate Copolymer

Lotte Chemical Corporation

PROSPECTOR®

www.ulprospector.com

Where to Buy

Supplier

Lotte Chemical Corporation

Seoul, Seoul South Korea

Telephone: +82-2-829-4114

Web: <http://english.lottechem.com/>

Distributor

Advanced Plastics, Inc

Telephone: 847-550-5556

Web: <http://www.apikolon.com/>

Availability: Mexico, North America, South America

RESINEX Group

RESINEX is a Pan European distribution company. Contact RESINEX for availability of individual products by country.

Telephone: +32-14-672511

Web: <http://www.resinex.com/>

Availability: Europe

